



GUANGZHOU MATEYS CHEMICALS LTD.

MED-550B High Cured Electrophonetic Paint

- (1) Newly kind of varnish of Acrylic Polyurethane in surface protection
- (2) Water-base paint
- (3) Perfect performance, robust
- (4) Anti-yellowish
- (5) High corrosion resistance
- (6) No heavy metal
- (7) Widely used in metal decorations, pens, lightings, smoking set, glasses and other hardware

1、 Composition & Conditions

(1) Performance

Items	Performance
Performance	Light yellow, Transparent
(0 ~ 40°C) EXP	12 months
Testing Method	Visual Inspection
Storage	Store in shady and cool again sun

(2) Standard

Composition	MED-550B	Testing Method
Solidcontent	10±2%	GB1725-79
pH Value	4.5±0.5 <25°C>	pH Meter
Conductivity	600±250 μS/cm <25°C>	Conductivity meter
Temperature	20 ~ 30°C	Actual Measurement
Voltage	20-120 V	Actual Measurement
Time	15-60 S	
Cure Condition	160±5/30 °C/min	Actual Temperature

Remarks. Pls kindly give us an email for more details.

ADD: 25 Jianhua Rd., Tianhe Software Park, Keyun Rd.,

Tianhe Dist., Guangzhou, China510665

TEL: +86 20 85576176/85555261/85555262

CEL: +86 13922181787 Skype: gzmateys

Email: gzmateys@qq.com gzmateys@163.com

URL: www.gzmateys.com/en gzmateys.en.alibaba.com