



GUANGZHOU MATEYS CHEMICALS LTD.

MT-833 Activation Agent

1、 Specifications

- (1) One kind of activation agent
- (2) Special for non-metal, ABS, PC, PC/ABS, PP, Nylon ect.
- (3) Form a uniform layer
- (4) Lower consumptions
- (5) Lower acid
- (6) Good stability
- (7) Used in chemical Nickel/Copper deposition

2、 Compositions & Conditions

Compositions	Perfect	Range
MT-833	20ml/L	10-30ml/L
MT-833B	920ml/L	900-940ml/L
HCl	60-100ml/L	
Temperature	26-28°C	25-45°C
Tank	PVC、PP	
Agitation	Mechanical rabble (continual or intermittent), 1-3µm filter element	
Heat	Heat with water pack. (No direct heat)	
STANDARD	0.5-0.8dm ² /L	

Remarks. Pls kindly give us an email for more details.

ADD: 25 Jianhua Rd., Tianhe Software Park, Keyun Rd.,

Tianhe Dist., Guangzhou, China510665

TEL: +86 20 85576176/85555261/85555262

CEL: +86 13922181787 Skype: gzmateys

Email: gzmateys@qq.com gzmateys@163.com

URL: www.gzmateys.com/en gzmateys.en.alibaba.com